



Revision Number: 001.0

Issue date: 07/29/2024

**1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER**

Product identifier used on the label: FP Kenra Volume Spray 25 50% VOC - Limited Edition - Sultry Nights

Recommended use of the chemical and restrictions on use: Hairspray, Aerosol

Name, address and telephone number of the chemical manufacturer:

Henkel Corporation  
One Henkel Way  
Rocky Hill CT 06067

CHEMTREC: 1-800-424-9300 (24 hours daily)  
Internet: www.henkel-northamerica.com

Emergency telephone number: Medical Emergencies:1-800-258-3425

**2. HAZARDS IDENTIFICATION**

The hazards described in this Globally Harmonized System Safety Data Sheet (SDS) are not intended for consumers, and does not address consumer use of the product. For information regarding consumer applications of this product, refer to the product label.

Classification of the substance or mixture in accordance with paragraph (d) of §1910.1200

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	1
GASES UNDER PRESSURE	Liquef. Gas
EYE IRRITATION	2A

Signal word, hazard statement(s), symbol(s) and precautionary statement(s) in accordance with paragraph (f) of §1910.1200

Signal word: DANGER  
 Hazard Statement(s):  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.

Symbol(s):

Precautionary Statements:

**Prevention:** Keep away from heat, sparks, open flames, hot surfaces - no smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Wash affected area thoroughly after handling.  
 Wear eye and face protection.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical attention.

**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50.DEGREE.C/122.DEGREE.F.

**Disposal:** Not prescribed

Hazards not otherwise classified: Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

The following chemicals are classified as health hazards in accordance with paragraph (d) of § 1910.1200.

Chemical Name*	CAS Number (Unique Identifier)	Concentration
Ethanol denatured	64-17-5	>= 30 - < 50 %
1,1-Difluoroethane	75-37-6	>= 30 - < 50 %

\*The specific chemical identity and/or exact percentage (concentration) of composition has been withheld because a trade secret is claimed in accordance with paragraph (i) of §1910.1200.

Actual concentration or concentration range is withheld as a trade secret

### 4. FIRST AID MEASURES

#### Description of necessary measures

**Inhalation:** Remove from exposure area to fresh air. Treat symptomatically and supportively.  
**Skin contact:** First aid measures not required.  
**Eye contact:** Rinse eyes with plenty of water until no evidence of product remains. Get medical attention if pain or irritation develops.  
**Ingestion:** Dilution by rinsing the mouth and giving water or milk to drink is generally recommended. Contact physician or local poison control center.

#### Most important symptoms and effects, both acute and delayed

After eye contact: May cause moderate to severe irritation. After skin contact: No adverse effects anticipated from normal use. After inhalation: Airborne concentrations of propane and isobutane, the propellants in this product, exceeding workplace standards may cause central nervous system effects and irritation of the throat and lungs with coughing, nausea and vomiting. After ingestion: Ingestion may cause irritation of mouth, throat, digestive tract, diarrhea and vomiting.

#### Indication of any immediate medical attention and special treatment needed

After eye contact: Immediately rinse eyes with plenty of water for at least 15 minutes while holding eyelids open. After skin contact: Rinse affected area with mild soap and water until no evidence of product remains. After inhalation: Immediately remove from exposure area to fresh air. Keep affected person warm and at rest. Treat symptomatically and supportively. Contact physician or local poison control center. If breathing has stopped, give artificial respiration, and get medical attention immediately. After ingestion: Administer immediately plenty of water. With ingestion of larger quantities (in adults one tablespoon) or in the case of discomfort or pain seek immediate medical attention.

### 5. FIRE FIGHTING MEASURES

#### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Dry chemical, carbon dioxide, water spray or regular foam.  
**Unsuitable extinguishing media:** None known

#### Specific hazards arising from the chemical

carbon oxides. nitrogen oxides

#### Special protective equipment and precautions for fire-fighters

In case of fire, wear a full-face positive-pressure self-contained breathing apparatus and protective suit. Shut off all ignition sources. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Isolate area. Keep unnecessary personnel away. Avoid breathing vapors, keep upwind.

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Wear skin, eye and respiratory protection as recommended in Section 8. Shut off ignition sources. Stop leak if you can do it without risk. Use water spray to reduce vapors. Isolate area until vapors have dispersed. No smoking, flames or flares in hazard area! Keep unnecessary people away; isolate hazard area and deny entry. Ventilate closed spaces before entering. Stay upwind; keep out of low areas.

## Environmental precautions

Small or household quantities may be disposed in regular domestic trash. For larger quantities check with your local disposal authorities.

## Methods and materials for containment and cleaning up

SMALL SPILLS: Contain and absorb with sand or other non-combustible absorbent material and place into containers for later disposal. Wash site of spillage thoroughly with water. LARGE SPILLS: Dike far ahead of spill to prevent further movement. Recover by pumping or by using a suitable absorbent material and place into containers for later disposal. Dispose in suitable waste container.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

Do not get in eyes. Do not take internally. Use with adequate ventilation. Have emergency equipment (for fires, spills, leaks, etc.) readily available.

### Conditions for safe storage, including any incompatibilities

Store in original containers in a cool dry area. Store away from excessive heat and incompatible substances. Storage areas for large quantities (warehouse) should be well ventilated. Keep the containers tightly closed when not in use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethanol denatured	1,000 ppm STEL	1,000 ppm (1,900 mg/m <sup>3</sup> ) PEL	None	None
1,1-Difluoroethane	None	None	1,000 ppm (2,700 mg/m <sup>3</sup> ) TWA	None

### Appropriate engineering controls

Provide local exhaust or general dilution ventilation to keep exposure to airborne contaminants below the permissible exposure limits where mists or vapors may be generated.

### Individual protection measures

<b>Respiratory:</b>	Air contamination monitoring should be carried out where mists or vapors are likely to be generated, to assure that the employees are not exposed to airborne contaminants above the permissible exposure limits.
<b>Eye:</b>	Splash-proof safety glasses are required to prevent eye contact where splashing of product may occur.
<b>Hand/Body:</b>	Protective gloves are required where repeated or prolonged skin contact may occur. Protective clothing is required where repeated or prolonged skin contact may occur.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	aerosolLiquefied gas
<b>Odor:</b>	colourless to yellowcolourless to yellow
<b>Odor threshold:</b>	characteristiccharacteristic
<b>pH:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Boiling point/range:</b>	Not available.
<b>Flash point:</b>	10 °C (50°F) ASTM D56: Flash point in closed cup
<b>Evaporation rate:</b>	Not available.
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Vapor pressure:</b>	Not available.
<b>Vapor density:</b>	Not available.
<b>Solubility in water:</b>	Partially soluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

**Viscosity:** Not available.  
**VOC content:** Not available.

## 10. STABILITY AND REACTIVITY

**Reactivity:** This product may react with strong acids, bases and oxidizing agents.

**Chemical stability:** Stable under normal ambient temperature (70°F, 21°C) and pressure (1 atm).

**Possibility of hazardous reactions:** Hazardous polymerization has not been reported to occur under normal temperatures and pressures.

**Conditions to avoid:** Avoid contact with incompatible substances, excessive heat, flames or other ignition sources. Exposure to sunlight or heat may cause bursting. Do not place aerosol cans in trash compactor. Contents are under pressure; containers may violently rupture and travel a considerable distance. Do not permit physical damage or overheating of containers.

**Incompatible materials:** Strong oxidizers and alkalies, chlorine, hypochlorites.

**Hazardous decomposition products:** Thermal decomposition may produce irritating or poisonous gases.

## 11. TOXICOLOGICAL INFORMATION

### Likely routes of exposure including symptoms related to characteristics

**Inhalation:** Breathing high vapor concentrations may produce anesthetic effects, nausea, dizziness, headache, weakness, peripheral drowsiness. Intentional inhalation of vapors from product may cause central nervous system effects and irritation of the throat and lungs with coughing.

**Skin contact:** No adverse effects anticipated from normal use.

**Eye contact:** May cause moderate to severe irritation.

**Ingestion:** May cause mild gastrointestinal irritation with nausea, vomiting, diarrhea and abdominal pain.

**Physical/Chemical:** The product is flammable.

**Other relevant toxicity information:** This product is a personal care or cosmetic product. The use of this product by consumers is safe under normal and reasonable foreseen use.

### Numerical measures of toxicity, including delayed and immediate effect

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Ethanol denatured	Oral LD50 (RAT) = 9.9 g/kg Oral LD50 (RAT) = 6.2 g/kg Oral LD50 (RAT) = 17.8 g/kg Oral LD50 (RAT) = 11.5 g/kg Oral LD50 (RAT) = 10.6 g/kg Oral LD50 (RAT) = 7,060 mg/kg Inhalation LC50 (RAT, 6 h) = 92.6 mg/l Inhalation LC50 (RAT, 6 h) = 51.3 mg/l Inhalation LC50 (RAT, 4 h) = 133.8 mg/l Inhalation LC50 (RAT, 6 h) = 82.1 mg/l Inhalation LC50 (RAT, 4 h) = 124.7 mg/l Inhalation LC50 (RAT, 6 h) = 52.9 mg/l Inhalation LC50 (RAT, 6 h) = 54.8 mg/l Inhalation LC50 (RAT, 4 h) = > 115.9 mg/l Inhalation LC50 (RAT, 6 h) = 87.5 mg/l Inhalation LC50 (RAT, 4 h) = 130.7 mg/l Inhalation LC50 (RAT, 4 h) = 128.2 mg/l Inhalation LC50 (RAT, 4 h) = 116.9 mg/l	Central nervous system, Irritant
1,1-Difluoroethane	Inhalation LC50 (RAT, 4 h) = > 437500 ppm	Cardiac, Central nervous system, Developmental, Irritant, Respiratory

### Carcinogenicity information

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Ethanol denatured	No	No	No
1,1-Difluoroethane	No	No	No

**Carcinogenicity**

None of the ingredients in this product are listed as carcinogens by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA).

**Mutagenicity**

None of the ingredients in this product are known to cause mutagenicity.

**Toxicity for reproduction**

None of the ingredients in this product are known as reproductive, fetal, or developmental hazards.

## 12. ECOLOGICAL INFORMATION

**Aquatic Toxicity:**

This product is anticipated to be safe for the environment at concentrations predicted in household settings under normal use conditions. The following toxicity information is available for the hazardous ingredient(s) when used as technical grade and is provided as reference for the occupational settings.

**Toxicity to fish:**

The aquatic toxicity profile of this product has not been determined.

**Chronic toxicity to aquatic invertebrates**

The aquatic toxicity profile of this product has not been determined.

**Toxicity to algae:**

The aquatic toxicity profile of this product has not been determined.

**Persistence and degradability**

Hazardous substances CAS-No.	Result value	Route of application	Species	Method
Ethanol denatured 64-17-5	readily biodegradable	aerobic	80 - 85 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1,1-Difluoroethane 75-37-6	not readily biodegradable.	aerobic	3 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

**Bioaccumulative potential**

The bioaccumulation potential of this product has not been determined.

**Mobility in soil**

The mobility of this product (in soil and water) has not been determined.

## 13. DISPOSAL CONSIDERATIONS

### Description of waste residues:

**Hazardous waste number:** D001 (Ignitability)

### Safe handling and disposal methods:

**Recommended method of disposal:** This product is a RCRA characteristic (ignitable) hazardous waste and must be disposed of in a RCRA Subtitle C landfill.

**Disposal of uncleaned packages:** Do not reuse this container. Properly deaerosolize any intact containers before disposal. Dispose of container and unused contents in accordance with federal, state and local requirements

## 14. TRANSPORT INFORMATION

The information in this section is for reference only and should not take the place of a shipping paper (bill of lading) specific to an order. Please note that the proper shipping classification may vary by packaging, properties, and mode of transportation.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Aerosols  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Aerosols, flammable  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** AEROSOLS  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

## 15. REGULATORY INFORMATION

**Occupational safety and health act:** Hazard Communication Standard, 29 CFR 1910.1200(g) Appendix D: The Occupational Safety and Health Administration (OSHA) require that the Safety Data Sheets (SDSs) are readily accessible to employees for all hazardous chemicals in the workplace. Since the use pattern and exposure in the workplace are generally not consistent with those experienced by consumers, this SDS may contain health hazard information not relevant to consumer use.

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.

**CERCLA/SARA Section 311/312:** Not available.

**CERCLA/SARA Section 313:** None above reporting de minimis.

**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

## 16. OTHER INFORMATION

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** R&D Support Services

**Issue date:** 07/29/2024



Revision Number: 001.0

Issue date: 07/29/2024

**1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER**

Product identifier used on the label: FP Kenra Volume Spray 25 80% VOC - Limited Edition - Sultry Nights

Recommended use of the chemical and restrictions on use: Hairspray, Aerosol

Name, address and telephone number of the chemical manufacturer:

Henkel Corporation  
One Henkel Way  
Rocky Hill CT 06067

CHEMTREC: 1-800-424-9300 (24 hours daily)  
Internet: www.henkel-northamerica.com

Emergency telephone number: Medical Emergencies:1-800-258-3425

**2. HAZARDS IDENTIFICATION**

The hazards described in this Globally Harmonized System Safety Data Sheet (SDS) are not intended for consumers, and does not address consumer use of the product. For information regarding consumer applications of this product, refer to the product label.

Classification of the substance or mixture in accordance with paragraph (d) of §1910.1200

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	1
GASES UNDER PRESSURE	Liquef. Gas
EYE IRRITATION	2A

Signal word, hazard statement(s), symbol(s) and precautionary statement(s) in accordance with paragraph (f) of §1910.1200

Signal word: DANGER  
 Hazard Statement(s):  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.

Symbol(s):

Precautionary Statements:

**Prevention:** Keep away from heat, sparks, open flames, hot surfaces - no smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Wash affected area thoroughly after handling.  
 Wear eye and face protection.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical attention.

**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50.DEGREE.C/122.DEGREE.F.

**Disposal:** Not prescribed

Hazards not otherwise classified: Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).



See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

The following chemicals are classified as health hazards in accordance with paragraph (d) of § 1910.1200.

Chemical Name*	CAS Number (Unique Identifier)	Concentration
Ethanol denatured	64-17-5	>= 30 - < 50 %
1,1-Difluoroethane	75-37-6	>= 20 - < 30 %
butane	106-97-8	>= 10 - < 20 %
Isobutane	75-28-5	>= 5 - < 10 %
propane	74-98-6	>= 1 - < 5 %

\*The specific chemical identity and/or exact percentage (concentration) of composition has been withheld because a trade secret is claimed in accordance with paragraph (i) of §1910.1200.

Actual concentration or concentration range is withheld as a trade secret

### 4. FIRST AID MEASURES

#### Description of necessary measures

**Inhalation:** Remove from exposure area to fresh air. Treat symptomatically and supportively.  
**Skin contact:** First aid measures not required.  
**Eye contact:** Rinse eyes with plenty of water until no evidence of product remains. Get medical attention if pain or irritation develops.  
**Ingestion:** Dilution by rinsing the mouth and giving water or milk to drink is generally recommended. Contact physician or local poison control center.

#### Most important symptoms and effects, both acute and delayed

After eye contact: May cause moderate to severe irritation. After skin contact: No adverse effects anticipated from normal use. After inhalation: Airborne concentrations of propane and isobutane, the propellants in this product, exceeding workplace standards may cause central nervous system effects and irritation of the throat and lungs with coughing, nausea and vomiting. After ingestion: Ingestion may cause irritation of mouth, throat, digestive tract, diarrhea and vomiting.

#### Indication of any immediate medical attention and special treatment needed

After eye contact: Immediately rinse eyes with plenty of water for at least 15 minutes while holding eyelids open. After skin contact: Rinse affected area with mild soap and water until no evidence of product remains. After inhalation: Immediately remove from exposure area to fresh air. Keep affected person warm and at rest. Treat symptomatically and supportively. Contact physician or local poison control center. If breathing has stopped, give artificial respiration, and get medical attention immediately. After ingestion: Administer immediately plenty of water. With ingestion of larger quantities (in adults one tablespoon) or in the case of discomfort or pain seek immediate medical attention.

### 5. FIRE FIGHTING MEASURES

#### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Dry chemical, carbon dioxide, water spray or regular foam.

**Unsuitable extinguishing media:** None known

#### Specific hazards arising from the chemical

carbon oxides. nitrogen oxides

#### Special protective equipment and precautions for fire-fighters

In case of fire, wear a full-face positive-pressure self-contained breathing apparatus and protective suit. Shut off all ignition sources. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Isolate area. Keep unnecessary personnel away. Avoid breathing vapors, keep upwind.

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Wear skin, eye and respiratory protection as recommended in Section 8. Shut off ignition sources. Stop leak if you can do it without risk. Use water spray to reduce vapors. Isolate area until vapors have dispersed. No smoking, flames or flares in hazard area! Keep unnecessary people away; isolate hazard area and deny entry. Ventilate closed spaces before entering. Stay upwind; keep out of low areas.

## Environmental precautions

Small or household quantities may be disposed in regular domestic trash. For larger quantities check with your local disposal authorities.

## Methods and materials for containment and cleaning up

SMALL SPILLS: Contain and absorb with sand or other non-combustible absorbent material and place into containers for later disposal. Wash site of spillage thoroughly with water. LARGE SPILLS: Dike far ahead of spill to prevent further movement. Recover by pumping or by using a suitable absorbent material and place into containers for later disposal. Dispose in suitable waste container.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

Do not get in eyes. Do not take internally. Use with adequate ventilation. Have emergency equipment (for fires, spills, leaks, etc.) readily available.

### Conditions for safe storage, including any incompatibilities

Store in original containers in a cool dry area. Store away from excessive heat and incompatible substances. Storage areas for large quantities (warehouse) should be well ventilated. Keep the containers tightly closed when not in use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethanol denatured	1,000 ppm STEL	1,000 ppm (1,900 mg/m <sup>3</sup> ) PEL	None	None
1,1-Difluoroethane	None	None	1,000 ppm (2,700 mg/m <sup>3</sup> ) TWA	None
butane	1,000 ppm STEL (Simple asphyxiant.)	None	None	None
Isobutane	1,000 ppm STEL	None	None	None
propane	D: Simple asphyxiant, EX: Explosion hazard (Simple asphyxiant.)	1,000 ppm (1,800 mg/m <sup>3</sup> ) PEL	None	None

### Appropriate engineering controls

Provide local exhaust or general dilution ventilation to keep exposure to airborne contaminants below the permissible exposure limits where mists or vapors may be generated.

### Individual protection measures

<b>Respiratory:</b>	Air contamination monitoring should be carried out where mists or vapors are likely to be generated, to assure that the employees are not exposed to airborne contaminants above the permissible exposure limits.
<b>Eye:</b>	Splash-proof safety glasses are required to prevent eye contact where splashing of product may occur.
<b>Hand/Body:</b>	Protective gloves are required where repeated or prolonged skin contact may occur. Protective clothing is required where repeated or prolonged skin contact may occur.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	aerosolLiquefied gas colourless to yellowcolourless to yellow
<b>Odor:</b>	characteristiccharacteristic
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Boiling point/range:</b>	Not available.
<b>Flash point:</b>	10 °C (50°F) ASTM D56: Flash point in closed cup
<b>Evaporation rate:</b>	Not available.
<b>Flammable/Explosive limits - lower:</b>	Not available.

<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Vapor pressure:</b>	Not available.
<b>Vapor density:</b>	Not available.
<b>Solubility in water:</b>	Partially soluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.
<b>Viscosity:</b>	Not available.
<b>VOC content:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	This product may react with strong acids, bases and oxidizing agents.
<b>Chemical stability:</b>	Stable under normal ambient temperature (70°F, 21°C) and pressure (1 atm).
<b>Possibility of hazardous reactions:</b>	Hazardous polymerization has not been reported to occur under normal temperatures and pressures.
<b>Conditions to avoid:</b>	Avoid contact with incompatible substances, excessive heat, flames or other ignition sources. Exposure to sunlight or heat may cause bursting. Do not place aerosol cans in trash compactor. Contents are under pressure; containers may violently rupture and travel a considerable distance. Do not permit physical damage or overheating of containers.
<b>Incompatible materials:</b>	Strong oxidizers and alkalies, chlorine, hypochlorites.
<b>Hazardous decomposition products:</b>	Thermal decomposition may produce irritating or poisonous gases.

## 11. TOXICOLOGICAL INFORMATION

### Likely routes of exposure including symptoms related to characteristics

<b>Inhalation:</b>	Breathing high vapor concentrations may produce anesthetic effects, nausea, dizziness, headache, weakness, peripheral drowsiness. Intentional inhalation of vapors from product may cause central nervous system effects and irritation of the throat and lungs with coughing.
<b>Skin contact:</b>	No adverse effects anticipated from normal use.
<b>Eye contact:</b>	May cause moderate to severe irritation.
<b>Ingestion:</b>	May cause mild gastrointestinal irritation with nausea, vomiting, diarrhea and abdominal pain.
<b>Physical/Chemical:</b>	The product is flammable.
<b>Other relevant toxicity information:</b>	This product is a personal care or cosmetic product. The use of this product by consumers is safe under normal and reasonable foreseen use.

**Numerical measures of toxicity, including delayed and immediate effect**

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Ethanol denatured	Oral LD50 (RAT) = 9.9 g/kg Oral LD50 (RAT) = 6.2 g/kg Oral LD50 (RAT) = 17.8 g/kg Oral LD50 (RAT) = 11.5 g/kg Oral LD50 (RAT) = 10.6 g/kg Oral LD50 (RAT) = 7,060 mg/kg Inhalation LC50 (RAT, 6 h) = 92.6 mg/l Inhalation LC50 (RAT, 6 h) = 51.3 mg/l Inhalation LC50 (RAT, 4 h) = 133.8 mg/l Inhalation LC50 (RAT, 6 h) = 82.1 mg/l Inhalation LC50 (RAT, 4 h) = 124.7 mg/l Inhalation LC50 (RAT, 6 h) = 52.9 mg/l Inhalation LC50 (RAT, 6 h) = 54.8 mg/l Inhalation LC50 (RAT, 4 h) = > 115.9 mg/l Inhalation LC50 (RAT, 6 h) = 87.5 mg/l Inhalation LC50 (RAT, 4 h) = 130.7 mg/l Inhalation LC50 (RAT, 4 h) = 128.2 mg/l Inhalation LC50 (RAT, 4 h) = 116.9 mg/l	Central nervous system, Irritant
1,1-Difluoroethane	Inhalation LC50 (RAT, 4 h) = > 437500 ppm	Cardiac, Central nervous system, Developmental, Irritant, Respiratory
butane	Inhalation LC50 (RAT, 10 min) = 1,442,738 mg/m <sup>3</sup> Inhalation LC50 (RAT, 10 min) = > 800000 ppm Inhalation LC50 (RAT, 10 min) = 1,443 mg/l	Cardiac, Central nervous system, Irritant
Isobutane	Inhalation LC50 (RAT, 10 min) = > 800000 ppm Inhalation LC50 (RAT, 10 min) = 1,443 mg/l Inhalation LC50 (RAT, 10 min) = 1,442,738 mg/m <sup>3</sup>	Cardiac, Central nervous system, Lung
propane	Inhalation LC50 (RAT, 10 min) = 1,354,944 mg/m <sup>3</sup> Inhalation LC50 (RAT, 4 h) = > 13023 ppm Inhalation LC50 (RAT, 10 min) = 1,355 mg/l Inhalation LC50 (RAT, 10 min) = 1,443 mg/l Inhalation LC50 (RAT, 10 min) = 570000 ppm Inhalation LC50 (RAT, 10 min) = 1,442,738 mg/m <sup>3</sup> Inhalation LC50 (RAT, 10 min) = > 800000 ppm Inhalation LC50 (RAT, 4 h) = > 13023 ppm	Cardiac, Central nervous system, Irritant

**Carcinogenicity information**

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Ethanol denatured	No	No	No
1,1-Difluoroethane	No	No	No
butane	No	No	No
Isobutane	No	No	No
propane	No	No	No

**Carcinogenicity**

None of the ingredients in this product are listed as carcinogens by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA).

**Mutagenicity**

None of the ingredients in this product are known to cause mutagenicity.

**Toxicity for reproduction**

None of the ingredients in this product are known as reproductive, fetal, or developmental hazards.

**12. ECOLOGICAL INFORMATION**

**Aquatic Toxicity:**

This product is anticipated to be safe for the environment at concentrations predicted in household settings under normal use conditions. The following toxicity information is available for the hazardous ingredient(s) when used as technical grade and is provided as reference for the occupational settings.

**Toxicity to fish:**

The aquatic toxicity profile of this product has not been determined.

**Chronic toxicity to aquatic invertebrates**

The aquatic toxicity profile of this product has not been determined.

**Toxicity to algae:**

The aquatic toxicity profile of this product has not been determined.

**Persistence and degradability**

Hazardous substances CAS-No.	Result value	Route of application	Species	Method
Ethanol denatured 64-17-5	readily biodegradable	aerobic	80 - 85 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1,1-Difluoroethane 75-37-6	not readily biodegradable.	aerobic	3 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Butane, n- (< 0.1 % butadiene) 106-97-8	readily biodegradable	aerobic	> 60 %	OECD 301 A - F
Isobutane 75-28-5	readily biodegradable	aerobic	> 60 %	OECD 301 A - F
Propane 74-98-6	readily biodegradable	aerobic	> 60 %	OECD 301 A - F

**Bioaccumulative potential**

The bioaccumulation potential of this product has not been determined.

**Mobility in soil**

The mobility of this product (in soil and water) has not been determined.

## 13. DISPOSAL CONSIDERATIONS

**Description of waste residues:**

**Hazardous waste number:** D001 (Ignitability)

**Safe handling and disposal methods:**

**Recommended method of disposal:** This product is a RCRA characteristic (ignitable) hazardous waste and must be disposed of in a RCRA Subtitle C landfill.

**Disposal of uncleaned packages:** Do not reuse this container. Properly deaerosolize any intact containers before disposal. Dispose of container and unused contents in accordance with federal, state and local requirements

## 14. TRANSPORT INFORMATION

The information in this section is for reference only and should not take the place of a shipping paper (bill of lading) specific to an order. Please note that the proper shipping classification may vary by packaging, properties, and mode of transportation.

**U.S. Department of Transportation Ground (49 CFR)**

**Proper shipping name:** Aerosols  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

**International Air Transportation (ICAO/IATA)**

**Proper shipping name:** Aerosols, flammable  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

**Water Transportation (IMO/IMDG)**

**Proper shipping name:** AEROSOLS  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**Occupational safety and health act:** Hazard Communication Standard, 29 CFR 1910.1200(g) Appendix D: The Occupational Safety and Health Administration (OSHA) require that the Safety Data Sheets (SDSs) are readily accessible to employees for all hazardous chemicals in the workplace. Since the use pattern and exposure in the workplace are generally not consistent with those experienced by consumers, this SDS may contain health hazard information not relevant to consumer use.

**United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Not available.  
**CERCLA/SARA Section 313:** None above reporting de minimis.

**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information**

**CEPA DSL/NDL Status:** One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

<b>16. OTHER INFORMATION</b>
------------------------------

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** R&D Support Services

**Issue date:** 07/29/2024